



**SHERWIN
WILLIAMS.**

105.45

DECKSCAPES®
Exterior Oil-Based
Semi-Transparent Stain
A18C50602

As of 12/01/12, Complies with:			
OTC	No	LEED® 09 CI	N/A
SCAQMD	No	LEED® 09 NC	N/A
CARB	No	LEED® 09 CS	N/A
CARB SCM 2007	No	LEED® H	N/A
MPI #	33	NGBS	N/A

<u>DESCRIPTION</u>	<u>CHARACTERISTICS</u>	<u>SURFACE PREPARATION</u>						
<ul style="list-style-type: none"> • Long-lasting penetrating oil-based formula protects the beauty of wood with a rich semi-transparent stain. • One coat coverage on most woods, do not apply a second coat • Scuff-resistant formula with maximum UV protection that resists fading. • Waterproofs to prevent moisture damage • This coating contains agents that inhibit the growth of mildew on the surface of this coating. <p>Use on wood:</p> <ul style="list-style-type: none"> • Decks • Doors • Siding • Fences • Shutters • Shingles • Shakes • Outdoor Furniture <p>Use on:</p> <ul style="list-style-type: none"> • Pressure treated wood • Cedar • Redwood • Pine • Oak • Plywood <p>Important: Stains tend to lap (dark lines where two freshly coated areas overlap). These tips will help avoid lap marks and keep the appearance uniform:</p> <ul style="list-style-type: none"> • Do not stain in direct sun or on a hot surface. • Stain from a dry area into the adjoining wet stain area. • Keep the leading edge wet and distribute the finish evenly. • Quickly remove puddles and excess material by redistributing to dry areas or wiping up. • Use natural breaks as boundaries to divide large areas into smaller, more manageable ones. • Stain a board from end to end. 	<p>Color: Semi-Transparent Stain colors A sample brushout is recommended to ensure color satisfaction.</p> <p>Coverage:</p> <p>Smooth Wood 250-300 sq ft/gal Rough Sawn Lumber 100-150 sq ft/gal Depending on porosity and texture Note: New wood normally requires less product than old, weathered wood. This is due to older wood being more porous than newer wood.</p> <p>Drying Time, @ 77°F, 50% RH</p> <p>To touch: 12 hours To recoat: BEFORE 24 hours To use: 24 hours</p> <p>Drying and recoat times are temperature, humidity, and film thickness dependent</p> <p>Due to the composition of DeckScapes Oil-Based Semi-Transparent, only one coat is necessary. On extremely porous wood, a second coat may be desired to uniform the finish. Excessive film build may create a glossy finish. If a second coat is needed, apply it within 24 hours of the first coat. If this 24 hour window is exceeded, the second coat may not penetrate and adhere properly. The surface must weather until water will not bead up on the surface before applying another coat.</p> <p>Flash Point: 121°F, PMCC Finish: no sheen Tinting with Blend-A-Color:</p> <table border="0"> <tr> <td>Base</td> <td>oz/gal</td> <td>Strength</td> </tr> <tr> <td>Tint Base</td> <td>½ - 6</td> <td>100%</td> </tr> </table> <p>Must be tinted, do not exceed 6 oz/gal of tinting color.</p> <p>Vehicle Type: alkyd A18C50602</p> <p>VOC (less exempt solvents): 511 g/L; 4.26 lb/gal</p> <p>Volume Solids: 34 ± 2% Weight Solids: 42 ± 2% Weight per Gallon: 7.4 lb</p>	Base	oz/gal	Strength	Tint Base	½ - 6	100%	<p>WARNING! Removal of old coatings by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.</p> <p>Clean all surfaces completely with the appropriate cleaner based on the conditions.</p> <p>DeckScapes Deck Wash</p> <ul style="list-style-type: none"> Mildew stain Algae stain Weathered wood (cleans wood) New deck material <p>DeckScapes Revive®</p> <ul style="list-style-type: none"> Tannin Bleed Nail stain Weathered wood (restores color) Gray wood (restores color) Mill Glaze <p>DeckScapes Stain & Sealer Remover Old Paint & Stain</p> <p>Carefully - Follow all label instructions. Thoroughly rinse the surface to remove all residue and allow to thoroughly dry before coating.</p> <p>Test the absorbency of the wood by sprinkling water on the surface. If the water penetrates into the wood quickly, the wood is ready to finish. If the water beads up or does not penetrate, allow the wood to weather 1 to 2 weeks and test for absorbency again.</p>
Base	oz/gal	Strength						
Tint Base	½ - 6	100%						



DECKSCAPES[®]

Exterior Oil-Based Semi-Transparent Stain A18C50602

<u>APPLICATION</u>	<u>COATING SOLUTION</u>	<u>CAUTIONS</u>
<p>Thoroughly stir contents before and occasionally during use. For uniformity, mix all cans together before use. Do not thin or mix with any other stains or coatings.</p> <p>Apply without thinning by brush, roller, pump sprayer or dip. When spraying and dipping, be sure to "back brush" to ensure uniform coverage. Penetration will vary depending on porosity and water content of the surface. Thoroughly coat cut ends and joints.</p> <p>For best results apply in shade with surface temperatures between 50°F and 90°F. Do not apply if temperatures will fall below 40°F or if rain is expected within 24 hours after application. Cooler temperatures require longer drying times.</p> <p><u>CLEAN UP INFORMATION</u></p> <p>Clean spills, spatters and tools immediately after use with mineral spirits. Follow manufacturer's safety recommendations when using mineral spirits.</p>	<p>Which product is the best for my project:</p> <p>DeckScapes Exterior Waterborne Clear</p> <ul style="list-style-type: none"> Protects wood from sun while allowing the wood to gray naturally Advanced water repellents make water bead up, protecting against cracking, splitting, and warping of wood. Leaves a protective coating that resists discoloration caused by mildew. <p>DeckScapes Exterior Oil Based Toner</p> <ul style="list-style-type: none"> Long-lasting, penetrating, oil-based formula Enriches wood appearance with a light tone UV protection resists graying Waterproofs to prevent moisture damage <p>DeckScapes Exterior Waterborne Semi-Transparent Deck Stain</p> <ul style="list-style-type: none"> Provides a long lasting, mildew-resistant film Excellent penetration for protecting horizontal exterior wood surfaces. Can be applied to damp surfaces, allowing surfaces to be prepared and stained in one day. <p>DeckScapes Ext. Oil-Based Semi-Transparent</p> <ul style="list-style-type: none"> Long-lasting penetrating formula protects the wood with a rich semi-transparent stain. One coat coverage on most woods Scuff-resistant formula with maximum UV protection that resists fading. Waterproofs to prevent moisture damage <p>DeckScapes Acrylic Solid Color Deck Stain</p> <ul style="list-style-type: none"> Water-based, 100% acrylic resin Provides mildew resistant coating Use over existing paint or stain Can be applied to damp surfaces, allowing surfaces to be prepped and stained in one day. <p>For Vertical surfaces - walls, siding, etc, use WoodScapes[®] Exterior Acrylic Solid Color Stain or WoodScapes[®] Exterior Polyurethane Semi-Transparent Stain.</p>	<p>This product must be applied outdoors to wood intended for exterior use only. Not for interior use. Do not use on roofs. Do not varnish or use a clear overcoat.</p> <p>LABEL CAUTIONS CAUTION contains ALIPHATIC HYDROCARBONS. Contents are COMBUSTIBLE. Keep away from heat and open flame. VAPOR HARMFUL. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. FIRST AID: In case of eye contact, flush thoroughly with large amounts of water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. In case of respiratory difficulty, provide fresh air and call physician. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN. DANGER: Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product, and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations. HOTW 04/01/2013 A18C50602 11 00</p> <p>The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Sherwin-Williams representative to obtain the most recent Product Data Sheet.</p>